

Inventory Accuracy, Visibility and Loss Prevention

Avery Dennison® 9906 Tabletop Bar Code Printer

Elevating Brands and Accelerating Performance Throughout the Global Retail Supply Chain



Avery Dennison® 9906 Tabletop Bar Code Printer

Standard Features

Dimensions

Height: 279 mm (11")
Width: 267 mm (10.5")
Depth: 409 mm (16.1")

Weight:

10 kg (22.1 lbs)

Shipping Weight:

11.4 kg (25 lbs)

Printing Method:

Thermal direct or Thermal transfer

Printhead:

Width: 102 mm/812 dots (4.09")
8 dots/mm/203 dpi
12 dots/mm/300 dpi

Memory:

Model BA:
4 MB Flash, 16 MB SDRAM
Model EF:
32 MB Flash, 32 MB SDRAM

Bar Codes:

UPCA +2/+5, UPCE +2/+5, EAN8 +2/+5, EAN13 +2/+5, EAN128 Interleaved 2 of 5, Extended Code 39, Codabar (NW7), Code 128, Code 16K, Code 93, MSI, Postnet, Intelligent Mail, GS1 Databar, PDF417, Maxi-Code, Data Matrix (ECC-200), Quick Response (QR Code), Aztec

Standard Fonts:

Bitmap - Standard, Reduced, Bold, OCRA-like, CG Triumvirate, and CG Triumvirate Bold
TrueType® - EFF Swiss Bold

Font Magnification:

1x to 7x for Bitmapped fonts, 4 to 250 pt. for scalable / TrueType™ fonts

Standard PC/Host Interface:

RS-232C Serial (115, 200 BPS)
USB 2.0 Host; USB 2.0 Device

Sensing Method:

Edge justified, die cut, black mark, aperture

Printer Control Language(s):

MPCL, Easyplug, MLI

Printer Warranty:

One (1) year parts and labour.
Full written warranty statement available upon request.

Printhead Warranty:

One (1) million inches or six (6) months, whichever occurs first

Supplies

Only Avery Dennison supplies are recommended.

Supply Types:

Labels and Tags

Supply Sizes:

Width: 19 mm to 114 mm (0.75" to 4.5")
Length: 13 mm to 1270 mm (0.50" to 50")
Width with peel: 38 mm to 108 mm (1.5" - 4.25")
Maximum length with indexed supplies: 445 mm (17.5")
Supply Roll OD: 8" on 3" core

Typical Supply Roll Length:

150 m (492')

Supply Thickness:

0.1397 mm to 0.2540 mm (0.0055" to 0.010")

Ribbon Length:

450 m (1476.38')

Environmental Ranges

Operating Temperature:

Thermal Transfer:
4° to 35°C (40° to 95°F)
Thermal Direct:
4° to 40°C (40° to 104°F)

Storage:

-10° to 49°C (15° to 120°F)

Humidity/Operating and Storage:

5% to 90% non-condensing

Electrostatic Discharge and Air Quality:

Some problems with electronic equipment may occur in environments prone to static discharge or extreme dust conditions. Avery Dennison suggests that you take precautions to minimize these problems.

Performance

Power Source:

90-264 VAC with
Auto select 50/60 Hz

Print Speed:

- 64 mm/s (2.5 ips) - default for serial bar codes
- 102 mm/s (4.0 ips)
- 152 mm/s (6.0 ips) - default for parallel bar codes

Option & Accessories

Options:

- Peel mode with on demand sensor
- Peel mode with liner take-up
- Tear bar with peel mode
- 300 dpi printhead
- ADK script programming for special applications
- Internal Ethernet with MonarchNet2™
- 802.11 b/g wireless with MonarchNet2™
- Parallel port (IEEE-1284)
- Tag cutter

Accessories:

- 935 Rewind
- 939i Keypad
- USB QWERTY keyboard
- 929 Tag catch tray

In our ongoing effort to deliver the best technology, specifications are subject to change without notice.

The information contained herein is believed to be reliable but Avery Dennison makes no representations concerning the accuracy or correctness of the data. This product, like any other, should be tested by the customer/user thoroughly under end user conditions to ensure the product meets the particular requirements. Independent results may vary. Avery Dennison and the logo are registered trademarks of Avery Dennison Corp. Third party trademarks and/or trade names used herein are the property of their respective owner(s). Avery Dennison liability is limited to the replacement value of defective products. In no event shall Avery Dennison be held liable for consequential, indirect or incidental damages. Products, information and specifications are subject to change without notice.

Avery Dennison and the logo are registered trademarks of Avery Dennison Corp. Third party trademarks and/or trade names used herein are the property of their respective owner(s).

© 2014 Avery Dennison Corporation, All Rights Reserved.

Avery Dennison Retail Branding and Information Solutions



GOMARO s.a. - CH 1123 Aclens - Switzerland

Tel: 021 869 97 70

Fax: 021 869 96 02

www.gomaro.ch

Contact info@gomaro.ch

www.rbis.averydennison.com

BRA330



Retail Branding and Information Solutions

0623SNG.EUKV01.1014A4.GRI